

DATA COMMUNICATION QUALITY CONTROL SYSTEM, TRANSMITTER SYSTEM AND RECEIVER

Publication number: WO0232083

Publication date: 2002-04-18

Inventor: NARUSE TETSUYA (JP)

Applicant: SONY CORP (JP); NARUSE TETSUYA (JP)

Classification:

- international: H04L1/00; H04L1/18; H04L5/14; H04L12/56; H04L27/26; H04Q7/38; H04Q7/32; H04L1/00; H04L1/16; H04L5/14; H04L12/56; H04L27/26; H04Q7/38; H04Q7/32; (IPC1-7): H04L29/08; H04L12/56; H04Q7/38

- European: H04Q7/38C8; H04L1/00A1M; H04L5/14R3; H04L12/56B; H04W28/18

Application number: WO2001JP08996 20011012

Priority number(s): US20000240182P 20001013

Also published as:

EP1237345 (A1)
EP1233594 (A1)
WO0232175 (A1)
WO0232082 (A1)
JP2007251978 (A)

more >>

Cited documents:


JP11355854
JP11088125
JP11355263
JP1170290
JP11187267

more >>

Report a data error here:

Abstract of WO0232083

An optimum communication quality in accordance with the type of data can be ensured between a transmitter system and a receiver. In a radio communication system (1) that controls the data communication quality between a transmitter system (2) that transmits contents and a mobile radio terminal (8) that receives the contents from the transmitter system (2) via a predetermined transmission path (15), the transmitter system (2) switches modulation methods in a data transmitting unit (13) in accordance with the type of the contents to be transmitted to the mobile radio terminal (8), thereby controlling the data communication quality between the transmitter system (2) and the mobile radio terminal (8). In this way, a data transmission from the transmitter system (2) to the mobile radio terminal (8) can be performed with a required data communication quality maintained by a modulation method that is the most suitable for the type of the contents.



Data supplied from the esp@cenet database - Worldwide

(12)特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関
国際事務局(43) 国際公開日
2002年4月18日 (18.04.2002)

PCT

(10) 国際公開番号
WO 02/32083 A1

(51) 国際特許分類: H04L 29/08, 12/56, H04Q 7/38

(21) 国際出願番号: PCT/JP01/08996

(22) 国際公開日: 2001年10月12日 (12.10.2001)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:
60/240,182 2000年10月13日 (13.10.2000) US

(71) 出願人 (発明者を除く全ての指定国について): ソニー株式会社 (SONY CORPORATION) [JP/JP]; 〒141-6001 東京都品川区北品川6丁目7番35号 Tokyo (JP).

(72) 発明者: および

(75) 発明者: 出願人 (米国についてのみ): 成瀬省也 (NARUSE, Tetsuya) [JP/JP]; 〒141-6001 東京都品川区北品川6丁目7番35号 ソニー株式会社内 Tokyo (JP).


(74) 代理人: 井理士 田辺恵基 (TANABE, Shigemasa); 〒150-0061 東京都渋谷区神宮前1丁目11番11-508号 グリーンフアンタジアビル5階 Tokyo (JP).

(81) 指定国 (国内): AE, AG, AL, AU, BA, BR, BG, BK, BZ, CA, CN, CO, CR, CU, CZ, DM, DZ, EC, EE, EG, GB, HR, HU, ID, IL, IN, IS, JP, KR, KZ, LC, LK, LR, LT, LV, MA, MG, MK, MN, MX, NO, NZ, PH, PL, RO, SG, SI, SK, TT, UA, US, UZ, VN, YU, ZA.

[続表有]

(54) Title: DATA COMMUNICATION QUALITY CONTROL SYSTEM, TRANSMITTER SYSTEM AND RECEIVER

(54) 発明の名称: データ通信品質制御システム、送信システム及び受信機



- 2...TRANSMITTER SYSTEM
- 3...SERVER
- 11...ENCODER UNIT
- 12...DATA STORING UNIT
- 14...TRANSMISSION CONTROL UNIT
- 13...DATA TRANSMITTING UNIT
- 4...BASE STATION
- 15...TRANSMISSION PATH
- 8...MOBILE RADIO TERMINAL
- 20...RECEPTION CONTROL UNIT
- 16...DATA RECEIVING UNIT
- 19...DISPLAY UNIT
- 18...DECODER UNIT
- 17...DATA STORING UNIT

(57) Abstract: An optimum communication quality in accordance with the type of data can be ensured between a transmitter system and a receiver. In a radio communication system (1) that controls the data communication quality between a transmitter system (2) that transmits contents and a mobile radio terminal (8) that receives the contents from the transmitter system (2) via a predetermined transmission path (15), the transmitter system (2) switches modulation methods in a data transmitting unit (13) in accordance with the type of the contents to be transmitted to the mobile radio terminal (8), thereby controlling the data communication quality between the transmitter system (2) and the mobile radio terminal (8). In this way, a data transmission from the transmitter system (2) to the mobile radio terminal (8) can be performed with a required data communication quality maintained by a modulation method that is the most suitable for the type of the contents.

[続表有]

WO 02/32083 A1